





Industrial Fans & Blowers



# PRODUCT SPECIFICATIONS SI160-2D-S2



NOTE:- ALL DIMENSION ARE IN MM.

SPECIFICATIONS (50 & 60 Hz)									
Volt (V) ±10%	Frequency (Hz)	Watt (W) ±10%	Current (A) ±10%	Speed (RPM) ±200	Capacitor (µF)	Air Vol. (m <sup>3</sup> /hr)	Air Vol. (CFM)	Noise (dBA)	Nt. Wt. (Kg)
415	50	125	0.22	2050	----	450	265	60	4.0
	60	149	0.24	2150		500	294	62	

MECHANICAL CHARACTERISTICS	
Impeller	G.I, Zinc Plated
Housing, Grill	Steel Powder Coated
Type Of Application	S1 Continuous Duty
Ingress Protection Rating	IP-44
Insulation Class	"F"
Bearing	Maintenance Free Ball Bearing
Permissible Ambient Temperature	-30° To +60°C
Manufacturing Standards	EN60335-1
Testing Standards	IS 4894-1987
Balancing Grade	IS 1940-1-2003, Grade 6.3
Noise	A-weighted overall sound power level Distance of 2 meter
Product Life	30,000 hours (At 40°C)



**Note:-**

- 1) All Information contained in this document is confidential and the property of ROTECH. Reproduction of this in any form is to be done with the specific permission of the company
- 2) In view of continuous improvement and upgradation of products, the design, the specification, dimensions and information contained herein are subject to change without notice.